
C1
2uF/400VAC
C2
2uF/400VAC
C3
2uF/400VAC
S1
S2
C7
2uF/400VAC
C8
2uF/400VAC
C9
2uF/400VAC
R1
3.3k
R2
3.3k
R3
2.2k
R4
3.3k
D1
1N4004
D3
1N4004
D5
1N4004
D2
1N4004
D4
1N4004
D6
1N4004
C4
4uF/400VAC
C5
4uF/400VAC
C6
4uF/400VAC
I1
I2
I3
I4
V1
600V
D7
D8
Q1
IRFP450
R5
3.3k
CON1
3-phase socket (female)
P1 (L1)
P2 (L2)
P3 (L3)
N
E (PE)
Doubly
Insulated
Cord
CON2
Requires
a resistive
load/coil
Connect your
load here.
Doesn't work with
transformers
and TV's without
modification.
Incandescent bulbs
need extra care.
Doubly
Insulated
Cord
Protective Earth
Plastic Insulating Box
CON3
Mains Flexible
Doubly
Insulated
Cord
CON4
3- phase plug (male)
P1 (L1)
P2 (L2)
P3 (L3)
N
E (PE)
Twibright Exciter
Advanced version
Licensed under GPDL
2007/07/17
Cook